



# ITYS ES

**Solution for electrical substations**  
from 1000 to 3000 VA - Electrical Substation

Single-phase UPS



GAMME 498\_A

## High protection and high availability

- The ITYS ES series is a range of compact UPS systems available in 1000, 2000 and 3000 VA models with on-line double conversion technology (VFI) with sinusoidal absorption.
- ITYS ES guarantees permanent regulation of the output voltage and frequency. This technology is compatible with all IT and industrial applications and operating environments, installations with generator sets included.
- Wide tolerance on input voltage ensures that switchovers to battery mode are infrequent, significantly prolonging battery lifetime.
- The automatic bypass device switches over in zero time in the event of overload or failure, guaranteeing uninterrupted services.

## Straightforward to install and easy to use

- The UPS is shipped ready for connection with internal batteries connected and charged.
- ITYS ES, with the manual bypass option is easy to install without any special plant engineering preparation, as it is equipped with built-in thermal protection.

- The LCD monitoring/control panel and a buzzer make the equipment extremely easy and intuitive to use. The graphic indicating the power distribution path shows at a glance whether or not the system is working as it should.
- Battery efficiency can be tested via the control panel or using dedicated software.

## Operating efficiency and versatility

- The versatility of these models makes them suitable for protecting critical devices in the industrial field.
- The standard equipment and communication accessories have been specially designed to satisfy the typical needs of installation or use in transformer cabins (i.e. tropicalized boards).
- In situations where automatic power management procedures are required, the communication software can be used to programme scheduled start-up and shutdown times.
- Restarting the UPS from the battery to power the DG before closing the main isolator.

### The solution for

- > Control devices
- > Electric lines

### Technology

- > VFI "online double conversion"

### Certifications



### Tech info

The CEI 016 STANDARD for auxiliary cabin equipment requires an uninterrupted power supply to the control circuits for the General Protection and Medium Voltage Switch.

The control circuits for the General Protection, Medium Voltage Switch and coil must be powered by the same auxiliary voltage when there is no power. The power supply must be guaranteed for a back-up time of 1 hour, either by the UPS or by buffer batteries.

The Medium Voltage Switch must be powered up by skilled personnel if out of service for a long time due to maintenance or failure.

It is necessary to power the General Protection before closing the Medium Voltage Switch.

The required protection comprises:

- Mains power cuts due to poor maintenance of the user's system.
- Inappropriate tripping of the Medium Voltage Switch because of faults in the trip circuit.
- Alert signalling if the Medium Voltage Switch trips due to a power failure (system with regular maintenance).

## UPS - Technical data

ITYS ES			
Sn [VA]	1000	2000	3000
Pn [W]	800	1600	2400
Input/output	1/1		
INPUT			
Rated voltage	230 V (110÷300 V)		
Rated frequency	50/60 Hz		
Power factor	0.98		
OUTPUT			
Rated voltage	208 / 220 / 230 / 240 V (± 2 %)		
Rated frequency	50 / 60 Hz (45÷55 Hz / 54÷66 Hz)		
Overload	up to 150 % for 10 seconds		
Crest factor	3:1		
Wiring	3 x IEC 320 (C13)	6 x IEC 320 (C13)	4 x IEC 320 (C13) + terminals
BATTERIES			
Type	sealed lead-acid maintenance free - expected lifetime 3-5 years		
Back-up time at 75% of the rated load <sup>(1)</sup>	10 minutes	17 minutes	9 minutes
Sized for a back-up time of	115 minutes @ 50 W	154 minutes @ 100 W	216 minutes @ 150 W
Back-up time <sup>(2)</sup> + switching back on	60 minutes @ 50 W	60 minutes @ 100 W	60 minutes @ 150 W
Battery test	•	•	•
COMMUNICATION			
Interfaces	RS232 - USB		
Ethernet adapter	NET VISION (TCP / IP & SNMP) optional card		
Local communication software	Local View		
EFFICIENCY			
Online mode	up to 92%		
ENVIRONMENT			
Ambient service temperature	from 0 °C up to +40 °C (from 15 °C to 25 °C for maximum battery lifetime)		
Relative humidity	< 95 % non-condensing		
Maximum altitude	1000 m without de-rating		
Noise level at 1 m	< 50 dBA		
UPS			
Dimensions W x D x H	145 x 400 x 220 mm	192 x 460 x 347 mm	
Weight	13 kg	31 kg	60 kg
Degree of protection	IP20		
COMPLIANCE WITH STANDARDS			
Safety	IEC/EN 62040-1, AS 62040.1.1, AS 62040.1.2		
EMC	IEC/EN 62040-2, AS 62040.2		
Product declaration	CE, RCM (E2376)		
ITYS ES - Manual bypass <sup>(3)</sup>			
Sn [VA]	1000	2000	3000
INPUT			
Type of terminals	CBD6		
Wire size	6 mm² max		
BYPASS			
Switching positions	1: UPS - 2: MAINS		
Switching time	6 ms max		
LOAD OUTPUT			
Type of terminals	CBD6		
Wire size	6 mm² max		
UPS SUPPLY OUTPUT			
Type of socket	IEC 320 10 A		IEC 320 16 A
SURGE ARRESTORS (on request)			
Type	"L" in compliance with CEI EN 61643-11		
L/N pulse current	40 kA (8/20) max		
VAC N/GND	255 V max		
VAC L / N	320 V max		

(1) @ 25 °C with charged battery.

(2) Factory setting: back-up time limited to 60 minutes to permit subsequent restarting with battery.

(3) Upon request.

## Standard communication features

- LOCAL VIEW: ideal UPS monitoring and shutdown point-to-point solution for Windows®, Linux and Mac OS X® operating systems.
- MODBUS/JBUS RTU (RS 232).

## Communication options

- NET VISION: professional WEB/SNMP interface for UPS monitoring and shutdown management of several operating systems.
- Dry contact interface.

## Manual bypass (option)

- Specially designed for ITYS ES, the manual bypass option enables:
- simplified installation: connection to the system is made with industrial grade terminals, while connection to the UPS is via the pre-wired plug and socket supplied.
- easy maintenance and uninterrupted operation: thanks to the manual bypass isolator it is possible to service or replace the UPS while maintaining the power supply to the devices downstream in complete safety for the operator. This operation has been specially devised to be simple to carry out, even in an emergency.
- increased level of equipment immunity to surge voltages, typical for this type of application, thanks to suitable surge arrestors included in addition to standard UPS protection.

